

What is claimed is:

1. An apparatus for controlling A/V outputs of a plurality of A/V players, the apparatus comprising:

5 a selection input unit for receiving target data that represents a target A/V display unit among a plurality of A/V display units and selection data which is used to select an A/V player among the plurality of A/V players for the target A/V display unit to generate a selection signal
10 corresponding to the selected A/V player and the target A/V display unit; and

a control unit for receiving the selection signal to control the selected A/V player so that an output of the selected A/V player is displayed on the target A/V display
15 unit.

2. The apparatus of claim 1, wherein the control unit further includes:

a micom for receiving the selection signal to generate
20 a control signal corresponding to the selected A/V player; and

a selection unit having a plurality of selection circuits which are respectively connected to the plurality of A/V display units, wherein a selection circuit among the

plurality of selection circuits is connected to the target A/V display unit and receives the control signal to control the selected A/V player so that an output of the selected A/V player is displayed on the target A/V display unit.

5

3. The apparatus of claim 1, wherein the control unit is implemented by one or more IC chips.

4. An apparatus for controlling A/V outputs of a plurality of A/V players, the apparatus comprising:

10 a selection input unit having a plurality of selection input subunits which are respectively connected to the plurality of A/V display units, wherein each selection input subunit receives selection data for selecting an A/V player among the plurality of A/V players to generate a selection
15 signal corresponding to the selected A/V player; and

a control unit for receiving the selection signal to control the selected A/V player so that an output of the selected A/V player is displayed on the target A/V display
20 unit.

5. The apparatus of claim 4, wherein the control unit further includes:

a micom for receiving the selection signal to generate

a control signal corresponding to the selected A/V player;
and

5 a selection unit having a plurality of selection
circuits which are respectively connected to the plurality
of A/V display units, wherein a selection circuit among the
plurality of selection circuits is connected to the target
A/V display unit and receives the control signal to control
the selected A/V player so that an output of the selected
A/V player is displayed on the target A/V display unit.

10

5. The apparatus of claim 4, wherein the control unit
further includes:

a micom for receiving the selection signal to thereby
generate a control signal corresponding to the selected A/V
15 player; and

a selection unit having a plurality of selection
circuits which are respectively connected to the plurality
of A/V display units, wherein a selection circuit connected
to the target A/V display unit receives the control signal
20 to control the selected A/V player so that an output of the
selected A/V player is displayed on the target A/V display
unit.

6. The apparatus of claim 4, wherein the control unit is
25 implemented by one or more IC chips.